Toll Free: 1-800-782-5752
Fax: 763-295-6601
E-mail: rfrucci@gosuburban.com
www.gosuburban.com

Sidewinder® Sleeve: 18411

Same coating on both sides

18411 Material Features

• Material:	1000 Denier Cordura, Double Coated with Proprietary High FR Neoprene Meets MIL-C-20696E, Type 2, Class 1
• Temperature Range:	-40° to +250° F, Momentary Spot Heat up to 800° F
• Abrasion:	Very Good/Excellent; Drag Abrasion from Welding Spall, Concrete Floor Meets ISO 6945 Specifications
• Puncture/Tear:	Excellent; Resists puncture or tear
• UV protection:	Excellent; Best Barrier, meets EN13758-1, top rating of 80 New
• Chemicals:	Excellent, unaffected by water, petro chemicals, sea water, oils, mild solvents
• Wicking	Excellent; non wicking
• Welding Sparks/Spall	Excellent; Resist and sheds sparks and hot spall

Typical Applications:

Excellent choice for weld cable or welding hose that is dragged on the floor. Resists sparks and hot spall. Also used in Sub-sea maintenance where barnacles, sea life and salt water can damage hoses. Assembled long lengths available for this type of application. Heavily used on off shore oil and drill rigs.